



QUITAPINTURAS UNIVERSAL
Code : 12133




Version: 7

Revision: 28/02/2023







Previous revision: 16/12/2022


Date of printing: 28/02/2023

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1	PRODUCT IDENTIFIER: QUITAPINTURAS UNIVERSAL Code : 12133 UFI: SPK2-U1T9-S001-NYR6
1.2	RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST: <u>Intended uses (main technical functions):</u> <input type="checkbox"/> Industrial <input checked="" type="checkbox"/> Professional <input checked="" type="checkbox"/> Consumers Paint remover. <u>Sectors of use:</u> Consumer uses (SU21), Professional uses (SU22), <u>Types of PCN use:</u> Paint removers, thinners and related auxiliaries. <u>Uses advised against:</u> This product is not recommended for any use or sector of use (industrial, professional or consumer) other than those previously listed as "Intended or identified uses". <u>Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006:</u> Not restricted.
1.3	DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET: PINTURAS ISAVAL, S.L. c/Velluters, Parcela 2-14- P.I. Casanova - 46394 Ribarroja del Turia (Valencia) ESPAÑA Phone number: +34 96 1640001 - Fax: +34 96 1640002 - www.isaval.es <u>- E-mail address of the person responsible for the Safety Data Sheet:</u> atencionalcliente@isaval.es
1.4	EMERGENCY TELEPHONE NUMBER: +34 96 1640001 8:00-18:00 h.  National Poisons Information Service (NPIS) - In England, Wales or Scotland: dial 111 - In N Ireland: contact your local GP or pharmacist during normal hours.

SECTION 2 : HAZARDS IDENTIFICATION

2.1	CLASSIFICATION OF THE SUBSTANCE OR MIXTURE: Classification of mixtures is carried out in accordance with the following principles: a) when data (tests) for the classification of mixtures are available, generally is carried out based on these data, b) in the absence of data (tests) for mixtures are generally used interpolation or extrapolation methods of assessing the risk, using the available data for mixtures similarly classified, and c) in the absence of tests and information which would allow to apply interpolation or extrapolation techniques, methods are used to classify risk assessment based on the data of the individual components in the mixture. The classification as corrosive has been carried out having in mind the criteria of corrosivity by pH. <u>Classification in accordance with Regulation (EU) No. 1272/2008~2021/849 (CLP):</u> DANGER:Flam. Liq. 2:H225 STOT SE 2:H371 Aquatic Chronic 3:H412																								
	<table border="1"> <thead> <tr> <th>Danger class</th> <th>Classification of the mixture</th> <th>Cat.</th> <th>Routes of exposure</th> <th>Target organs</th> <th>Effects</th> </tr> </thead> <tbody> <tr> <td>Physicochemical: </td> <td>Flam. Liq. 2:H225 c)</td> <td>Cat.2</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>Human health: </td> <td>STOT SE 2:H371 c)</td> <td>Cat.2</td> <td>Ingestion</td> <td>Optic nerve, CNS</td> <td>Loss of vision</td> </tr> <tr> <td>Environment:</td> <td>Aquatic Chronic 3:H412 c)</td> <td>Cat.3</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Danger class	Classification of the mixture	Cat.	Routes of exposure	Target organs	Effects	Physicochemical: 	Flam. Liq. 2:H225 c)	Cat.2	-	-	-	Human health: 	STOT SE 2:H371 c)	Cat.2	Ingestion	Optic nerve, CNS	Loss of vision	Environment:	Aquatic Chronic 3:H412 c)	Cat.3	-	-	-
Danger class	Classification of the mixture	Cat.	Routes of exposure	Target organs	Effects																				
Physicochemical: 	Flam. Liq. 2:H225 c)	Cat.2	-	-	-																				
Human health: 	STOT SE 2:H371 c)	Cat.2	Ingestion	Optic nerve, CNS	Loss of vision																				
Environment:	Aquatic Chronic 3:H412 c)	Cat.3	-	-	-																				
	Full text of hazard statements mentioned is indicated in section 16. Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.																								

2.2	LABEL ELEMENTS:  This product is labelled with the signal word DANGER in accordance with Regulation (EU) No. 1272/2008~2021/849 (CLP)
	<u>- Hazard statements:</u> H225 Highly flammable liquid and vapour. H371 May cause damage to optic nerve and central nervous system if swallowed. H412 Harmful to aquatic life with long lasting effects.
	<u>- Precautionary statements:</u> P101 If medical advice is needed, have product container or label at hand. P102-P405 Keep out of reach of children. Store locked up. P103 Read label before use. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280 Wear protective gloves, clothing and eye protection. In case of inadequate ventilation wear respiratory protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower] P273-P501 Avoid release to the environment. Dispose of contents/container in accordance with local regulations.
	<u>- Supplementary statements:</u>
	<u>- Substances that contribute to classification:</u>



QUITAPINTURAS UNIVERSAL
Code : 12133



Version: 7

Revision: 28/02/2023

Previous revision: 16/12/2022

Date of printing: 28/02/2023

Methanol

2.3

OTHER HAZARDS:

Hazards which do not result in classification but which may contribute to the overall hazards of the mixture:

- Other physicochemical hazards:

Vapours may form with air a mixture potentially flammable or explosive.

- Other adverse human health effects:

Prolonged exposure to vapours may produce transient drowsiness. Prolonged contact may cause skin dryness.

- Other negative environmental effects:

Does not contain substances that fulfil the PBT/vPvB criteria.

Endocrine disrupting properties:

This product contains substances with endocrine disrupting properties under evaluation in a concentration equal to or greater than 0.1% by weight: Formic acid.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1

SUBSTANCES:

Not applicable (mixture).

3.2

MIXTURES:

This product is a mixture.

Chemical description:

Mixture of organic solvents.

HAZARDOUS INGREDIENTS:

Substances taking part in a percentage higher than the exemption limit:

60 < C < 70 %	1,3-dioxolane CAS: 646-06-0, EC: 211-463-5, REACH: 01-2119490744-29 CLP: Danger: Flam. Liq. 2:H225	REACH / CLP00	
20 < C < 25 %	Dimethoxymethane CAS: 109-87-5, EC: 203-714-2, REACH: 01-2119664781-31 CLP: Danger: Flam. Liq. 2:H225	Autoclassified REACH	
2,5 < C < 5 %	Hydrocarbons C9 aromatics CAS: 64742-95-6, EC: 918-668-5, REACH: 01-2119455851-35 CLP: Danger: Flam. Liq. 3:H226 STOT SE (irrit.) 3:H335 STOT SE (narcosis) 3:H336 Asp. Tox. 1:H304 Aquatic Chronic 2:H411 EUH066	Autoclassified REACH	
1 < C < 2 %	Formic acid CAS: 64-18-6, EC: 200-579-1, REACH: 01-2119491174-37 CLP: Danger: Flam. Liq. 3:H226 Acute Tox. (inh.) 3:H331 Acute Tox. (oral) 4:H302 Skin Corr. 1A:H314 Eye Dam. 1:H318 EUH071 (Note B)	REACH	Skin Corr. 1A, H314: C ≥90 % Skin Corr. 1B, H314: 10 % ≤ C < 90 % Skin Irrit. 2, H315: 2 % ≤ C < 10 % Eye Irrit. 2, H319: 2 % ≤ C < 10 %
1 < C < 2 %	Methanol CAS: 67-56-1, EC: 200-659-6, REACH: 01-2119433307-44 CLP: Danger: Flam. Liq. 2:H225 Acute Tox. (inh.) 3:H331 Acute Tox. (skin) 3:H311 Acute Tox. (oral) 3:H301 STOT SE 1:H370	REACH / CLP00	STOT SE 1, H370oQJ: C ≥10 % STOT SE 2, H371oQJ: 3 % ≤ C < 10 %

Impurities:

Does not contain other components or impurities which will influence the classification of the product.

Stabilizers:

None.

Reference to other sections:

For more information on hazardous ingredients, see sections 8, 11, 12 and 16.

SUBSTANCES OF VERY HIGH CONCERN (SVHC):

List updated by ECHA on 10/06/2022.

Substances SVHC subject to authorisation, included in Annex XIV of Regulation (EC) no. 1907/2006:

None.

Substances SVHC candidate to be included in Annex XIV of Regulation (EC) no. 1907/2006:

None.

PERSISTENT, BIOACCUMULABLE AND TOXIC PBT, OR VERY PERSISTENT AND VERY BIOACCUMULABLE VPVB SUBSTANCES:

Does not contain substances that fulfil the PBT/vPvB criteria.



QUITAPINTURAS UNIVERSAL
Code : 12133





Version: 7

Revision: 28/02/2023

Previous revision: 16/12/2022

Date of printing: 28/02/2023

SECTION 4: FIRST AID MEASURES

4.1	DESCRIPTION OF FIRST AID MEASURES:	
	 Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.	
	Route of exposure	Symptoms and effects, acute and delayed
	Inhalation:	It is not expected that symptoms will occur under normal conditions of use.
	Skin:	Prolonged contact may cause skin dryness.
	Eyes:	Contact with the eyes produces redness and pain.
	Ingestion:	If swallowed in high doses, may cause gastrointestinal disturbances.
		
		Description of first-aid measures
		Should there be any symptoms, transfer the person affected to the open air.
		Remove contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and a solution of 5% sodium bicarbonate. Finally, rewash the affected area with soap and water. Do not use solvents or thinners.
		Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water, holding the eyelids apart. If irritation persists, consult a physician.
		Due to its acid condition, the effects can be reduced to a minimum by drinking plenty of water, to which milk of magnesia has been added. Do not induce vomiting, due to the risk of aspiration. Keep the patient at rest.
4.2	MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:	
	The main symptoms and effects are indicated in sections 4.1 and 11.1	
4.3	INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:	
	Notes to physician: Treatment should be directed at the control of symptoms and the clinical condition of the patient.. Antidotes and contraindications: Specific antidote not known.	

SECTION 5: FIREFIGHTING MEASURES

5.1	EXTINGUISHING MEDIA:
	Extinguishing powder or CO ₂ .
5.2	SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:
	# As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, Carbon dioxide, formaldehyde. Exposure to combustion or decomposition products may be a hazard to health.
5.3	ADVICE FOR FIREFIGHTERS:
	Special protective equipment: Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or is not being used, combat fire from a sheltered position or from a safe distance. The standard EN469 provides a basic level of protection for chemical incidents. Other recommendations: Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.



QUITAPINTURAS UNIVERSAL
Code : 12133



Version: 7

Revision: 28/02/2023

Previous revision: 16/12/2022

Date of printing: 28/02/2023

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1	PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES: Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product. Avoid breathing vapours. Keep people without protection in opposition to the wind direction.
6.2	ENVIRONMENTAL PRECAUTIONS: Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.
6.3	METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP: Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc.). Transfer to a suitable container for recovery or elimination. Neutralize with carbonate or sodium bicarbonate. Finally, clean up the area with plenty of water. Keep the remains in a closed container.
6.4	REFERENCE TO OTHER SECTIONS: For contact information in case of emergency, see section 1. For information on safe handling, see section 7. For exposure controls and personal protection measures, see section 8. For waste disposal, follow the recommendations in section 13.

SECTION 7: HANDLING AND STORAGE

7.1	<p>PRECAUTIONS FOR SAFE HANDLING: Comply with the existing legislation on health and safety at work.</p> <p><u>- General recommendations:</u> Avoid any type of leakage or escape. Keep the container tightly closed.</p> <p><u>- Recommendations for the prevention of fire and explosion risks:</u> Vapours are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reach distant ignition sources and flame up or explode. Due to its flammability, this material should only be used in areas from which all naked lights and other sources of ignition have been excluded and away from other heat or electrical sources. Switch mobile phones off and do not smoke. No tools with a potential for sparks should be used.</p> <p>Flashpoint -19* °C (Pensky-Martens) CLP 2.6.4.3. Autoignition temperature: Not applicable. Ventilation requirement: Not available.</p> <p><u>- Recommendations for the prevention of toxicological risks:</u> Do not eat, drink or smoke while handling. After handling, wash hands with soap and water. For exposure controls and personal protection measures, see section 8.</p> <p><u>- Recommendations for the prevention of environmental contamination:</u> # Avoid any spillage in the environment. Pay special attention to the cleaning water. In the case of accidental spillage, follow the instructions indicated in section 6.</p>
7.2	<p>CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES: Forbid the entry to unauthorized persons. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area. If possible, avoid direct contact with sunlight. Avoid extreme humidity conditions. In order to avoid leakages, the containers, after use, should be closed carefully and placed in a vertical position. For more information, see section 10.</p> <p><u>- Class of store:</u> According to current legislation.</p> <p><u>- Maximum storage period:</u> 12 Months.</p> <p><u>- Temperature interval:</u> min:5 °C, max:40 °C (recommended).</p> <p><u>- Incompatible materials:</u> Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.</p> <p><u>- Type of packaging:</u> According to current legislation.</p> <p><u>- Limit quantity (Seveso III): Directive 2012/18/EU:</u> Not applicable (product for non industrial use).</p>
7.3	<p>SPECIFIC END USE(S): For the use of this product particular recommendations apart from that already indicated are not available.</p>



QUITAPINTURAS UNIVERSAL
Code : 12133



Version: 7

Revision: 28/02/2023

Previous revision: 16/12/2022

Date of printing: 28/02/2023

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1

CONTROL PARAMETERS:

If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

- OCCUPATIONAL EXPOSURE LIMIT VALUES (WEL)

EH40/2005 WELs (United Kingdom) 2018	Year	WEL-TWA		WEL-STEL		Remarks
		ppm	mg/m ³	ppm	mg/m ³	
1,3-dioxolane	2002	20	61	-	-	
Dimethoxymethane	1987	1000	3110	-	-	
Hydrocarbons C9 aromatics	-	50	290	-	-	Recommended
Formic acid	1987	5	9,4	10	19	
Methanol	2009	200	262	250	328	BMGV, Sk

WEL - Workplace Exposure Limit, TWA - Time Weighted Average (8 hours), STEL - Short Term Exposure Limit (15 min).

BMGV - Biological monitoring guidance value. BMGVs are non-statutory and any biological monitoring undertaken in association with a guidance value needs to be conducted on a voluntary basis (ie with the fully informed consent of all concerned).

Sk - Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

- Dermal (Sk):

Means that, in exposures to this substance, the contribution by the cutaneous route, including the mucous membranes and eyes, may result significant for the overall body content if no measures are taken to prevent absorption. There are some chemicals for which dermal absorption, both in liquid and vapour phases, can be very high, and this route of entry may be or equal or greater importance even that inhalation pathway. In these situations, the use of a biological control is essential in order to quantify the overall amount of contaminant absorbed.

- BIOLOGICAL LIMIT VALUES:

Biological monitoring can be a very useful complementary technique to air monitoring when air sampling techniques alone may not give a reliable indication of exposure. Biological monitoring is the measurement and assessment of hazardous substances or their metabolites in tissues, secretions, excreta or expired air, or any combination of these, in exposed workers. Measurements reflect absorption of a substance by all routes. Biological monitoring may be particularly useful in circumstances where there is likely to be significant skin absorption and/or gastrointestinal tract uptake following ingestion, where control of exposure depends on respiratory protective equipment, where there is a reasonably well-defined relationship between biological monitoring and effect, or where it gives information on accumulated dose and target organ body burden which is related to toxicity.

This preparation contains the following substances that have established a biological limit value:

-

- DERIVED NO-EFFECT LEVEL (DNEL):

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from an occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

- DERIVED NO-EFFECT LEVEL, WORKERS:- Systemic effects, acute and chronic:	DNEL Inhalation mg/m ³	DNEL Cutaneous mg/kg bw/d	DNEL Oral mg/kg bw/d
Hydrocarbons C9 aromatics	- (a) 150 (c)	- (a) 25 (c)	- (a) - (c)
Dimethoxymethane	s/r (a) 126,6 (c)	s/r (a) 17,9 (c)	- (a) - (c)
1,3-dioxolane	s/r (a) 3,306 (c)	s/r (a) 1,18 (c)	- (a) - (c)
Methanol	260 (a) 260 (c)	40 (a) 40 (c)	- (a) - (c)
Formic acid	19 (a) 9,5 (c)	s/r (a) s/r (c)	- (a) - (c)
- DERIVED NO-EFFECT LEVEL, WORKERS:- Local effects, acute and chronic:	DNEL Inhalation mg/m ³	DNEL Cutaneous mg/cm ²	DNEL Eyes mg/cm ²
Hydrocarbons C9 aromatics	- (a) - (c)	- (a) - (c)	- (a) - (c)
Dimethoxymethane	s/r (a) s/r (c)	s/r (a) s/r (c)	s/r (a) - (c)
1,3-dioxolane	s/r (a) s/r (c)	s/r (a) s/r (c)	m/r (a) - (c)
Methanol	260 (a) 260 (c)	- (a) - (c)	- (a) - (c)
Formic acid	19 (a) 9,5 (c)	s/r (a) s/r (c)	a/r (a) - (c)
- DERIVED NO-EFFECT LEVEL, GENERAL POPULATION:- Systemic effects, acute and chronic:	DNEL Inhalation mg/m ³	DNEL Cutaneous mg/kg bw/d	DNEL Eyes mg/kg bw/d
Hydrocarbons C9 aromatics	- (a) 32 (c)	- (a) 11 (c)	- (a) 11 (c)
Dimethoxymethane	s/r (a) 31,5 (c)	s/r (a) 18,1 (c)	s/r (a) 18,1 (c)
1,3-dioxolane	s/r (a) 4,52 (c)	s/r (a) 1,31 (c)	s/r (a) 1,31 (c)
Methanol	50 (a) 50 (c)	8 (a) 8 (c)	8 (a) 8 (c)
Formic acid	9,5 (a) 3 (c)	s/r (a) s/r (c)	s/r (a) s/r (c)
- LOCAL EFFECTS, ACUTE AND CHRONIC:- Local effects, acute and chronic:	DNEL Inhalation mg/m ³	DNEL Cutaneous mg/cm ²	DNEL Eyes mg/cm ²
Hydrocarbons C9 aromatics	- (a) - (c)	- (a) - (c)	- (a) - (c)



QUITAPINTURAS UNIVERSAL
Code : 12133



Version: 7

Revision: 28/02/2023

Previous revision: 16/12/2022

Date of printing: 28/02/2023

Dimethoxymethane	s/r (a)	s/r (c)	s/r (a)	s/r (c)	s/r (a)	- (c)
1,3-dioxolane	s/r (a)	s/r (c)	s/r (a)	s/r (c)	m/r (a)	- (c)
Methanol	50 (a)	50 (c)	- (a)	- (c)	- (a)	- (c)
Formic acid	9,5 (a)	3 (c)	s/r (a)	s/r (c)	- (a)	- (c)

(a) - Acute, short-term exposure, (c) - Chronic, long-term or repeated exposure.

(-) - DNEL not available (without data of registration REACH).

s/r - DNEL not derived (not identified hazard).

m/r - DNEL not derived (medium hazard).

a/r - DNEL not derived (high hazard).

- PREDICTED NO-EFFECT CONCENTRATION (PNEC):

<u>- PREDICTED NO-EFFECT CONCENTRATION, AQUATIC ORGANISMS:- Fresh water, marine water and intermittent release:</u>	<u>PNEC Fresh water</u> mg/l	<u>PNEC Marine</u> mg/l	<u>PNEC Intermittent</u> mg/l
Hydrocarbons C9 aromatics	-7	-7	-7
Dimethoxymethane	14.577	1.477	-
1,3-dioxolane	19.7	1.97	0.95
Methanol	154	15.4	1540
Formic acid	2	0.2	1

<u>- WASTEWATER TREATMENT PLANTS (STP) AND SEDIMENTS IN FRESH- AND MARINE WATER:</u>	<u>PNEC STP</u> mg/l	<u>PNEC Sediments</u> mg/kg dw/d	<u>PNEC Sediments</u> mg/kg dw/d
Hydrocarbons C9 aromatics	-7	-7	-7
Dimethoxymethane	10000	13.135	1.3135
1,3-dioxolane	1	77.7	7.77
Methanol	100	570.4	-
Formic acid	7.2	13.4	1.34

<u>- PREDICTED NO-EFFECT CONCENTRATION, TERRESTRIAL ORGANISMS:- Air, soil and effects for predators and humans:</u>	<u>PNEC Air</u> mg/m3	<u>PNEC Soil</u> mg/kg dw/d	<u>PNEC Oral</u> mg/kg dw/d
Hydrocarbons C9 aromatics	-7	-7	-7
Dimethoxymethane	2	4.6538	n/b
1,3-dioxolane	s/r	2.62	n/b
Methanol	-	23.5	-
Formic acid	-	1.5	-

(-) - PNEC not available (without data of registration REACH).

n/b - PNEC not derived (not bioaccumulative potential).

s/r - PNEC not derived (not identified hazard).

8.2

EXPOSURE CONTROLS:
ENGINEERING MEASURES:

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.

- Protection of respiratory system:

Avoid the inhalation of vapours.

- Protection of eyes and face:

It is recommended to install water taps or sources with clean water close to the working area.

- Protection of hands and skin:

It is recommended to install water taps or sources with clean water close to the working area. Barrier creams may help to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.

OCCUPATIONAL EXPOSURE CONTROLS: REGULATION (EU) NO. 2016/425:

As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding marking. For more information on personal protective equipment (storage, use, cleaning, maintenance, type and characteristics of the PPE, protection class, marking, category, CEN norm, etc..), you should consult the informative brochures provided by the manufacturers of PPE.

Mask: 	✓ AX-type filter mask (brown) for gases and vapours of organic compounds with a boiling point less or equal to 65°C (EN14387), with single-use filters. Class 1: low capacity up to 1000 ppm, Class 2: medium capacity up to 5000 ppm, Class 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers.
Safety goggles: 	✓ Safety goggles designed to protect against liquid splashes, with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.
Face shield:	No.



QUITAPINTURAS UNIVERSAL
Code : 12133




Version: 7

Revision: 28/02/2023

Previous revision: 16/12/2022

Date of printing: 28/02/2023

Gloves: 	✓ Gloves resistant against chemicals (EN374).When repeated or prolonged contact with the product is expected, gloves of protection level 5 or higher should be used, with a breakthrough time of >240 min.When short contact with the product is expected, use gloves with a protection level 2 or higher should be used, with a breakthrough time >30 min.The breakthrough time of the selected glove material should be in accordance with the pretended period of use.There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374.Due to the wide variety of circumstances and possibilities, the instructions/specifications provided by the glove supplier should be taken into account.Use the proper technique of removing gloves (without touching glove's outer surface) to avoid contact of the product with the skin.The gloves should be immediately replaced when any sign of degradation is noted.
Boots:	No.
Apron:	No.
Clothing:	Advisable.

- Thermal hazards:

Not applicable (the product is handled at room temperature).

ENVIRONMENTAL EXPOSURE CONTROLS:

Avoid any spillage in the environment. Avoid any release into the atmosphere.

- Spills on the soil:

Prevent contamination of soil.

- Spills in water:

Do not allow to escape into drains, sewers or water courses.

-Water Management Act:

This product does not contain any substance included in the list of priority substances in the field of water policy under Directive 2000/60/EC~2013/39/EU.

- Emissions to the atmosphere:

Because of volatility, emissions to the atmosphere while handling and use may result. Avoid any release into the atmosphere.



QUITAPINTURAS UNIVERSAL
Code : 12133



Version: 7

Revision: 28/02/2023

Previous revision: 16/12/2022

Date of printing: 28/02/2023

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1	<p>INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:</p> <p><u>Appearance</u> Physical state: Liquid Colour: Colourless Odour: Characteristic Odour threshold: Not available (mixture).</p> <p><u>Change of state</u> Melting point: Not available (mixture). Initial boiling point: 42,3* °C at 760 mmHg</p> <p><u>- Flammability:</u> Flashpoint: -19* °C (Pensky-Martens) CLP 2.6.4.3. Lower/upper flammability or explosive limits: Not available - Not available Autoignition temperature: Not applicable.</p> <p><u>Stability</u> Decomposition temperature: Not available (technical impossibility to obtain the data).</p> <p><u>pH-value</u> pH: Not applicable</p> <p><u>- Viscosity:</u> Dynamic viscosity: 25 Poise at 20°C Kinematic viscosity: 861,7 cSt at 20°C Viscosity (flow time): 60 sec. CF6 at 20°C</p> <p><u>- Solubility(ies):</u> Solubility in water: Immiscible Liposolubility: Not applicable (inorganic product). Partition coefficient: n-octanol/water: Not applicable (mixture).</p> <p><u>- Volatility:</u> Vapour pressure: 133,8424* mmHg at 20°C Vapour pressure: 70,2807* kPa at 50°C Evaporation rate: Not available (lack of data).</p> <p><u>Density</u> Relative density: 0,994* at 20/4°C Relative water Relative vapour density: 2,56* at 20°C 1 atm. Relative air</p> <p><u>Particle characteristics</u> Particle size: Not applicable.</p> <p><u>- Explosive properties:</u> Vapours can form explosive mixtures with air and are able to flame up or explode in presence of an ignition source.</p> <p><u>- Oxidizing properties:</u> Not classified as oxidizing product.</p> <p>*Estimated values based on the substances composing the mixture.</p>
9.2	<p>OTHER INFORMATION:</p> <p><u>Information regarding physical hazard classes</u> Flammable liquids: Combustibility: Combustible.</p> <p><u>Other security features:</u> Heat of combustion: Not applicable. VOC (supply): 96,7 % Weight VOC (supply): 961,3 g/l Nonvolatile: 3,03 * % Weight 1h. 60°C</p> <p>The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the corresponding technical data sheet. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.</p>



QUITAPINTURAS UNIVERSAL
Code : 12133



Version: 7

Revision: 28/02/2023

Previous revision: 16/12/2022

Date of printing: 28/02/2023

SECTION 10: STABILITY AND REACTIVITY

10.1	<p>REACTIVITY:</p> <p>- Corrosivity to metals: It is not corrosive to metals.</p> <p>- Pyrophorical properties: It is not pyrophoric.</p>
10.2	<p>CHEMICAL STABILITY: Stable under recommended storage and handling conditions.</p>
10.3	<p>POSSIBILITY OF HAZARDOUS REACTIONS: Possible dangerous reaction with oxidizing agents, alkalis, amines, reducing agents, acids.</p>
10.4	<p>CONDITIONS TO AVOID:</p> <p>- Heat: Keep away from sources of heat.</p> <p>- Light: If possible, avoid direct contact with sunlight.</p> <p>- Air: The product is not affected by exposure to air, but should not be left the containers open.</p> <p>- Humidity: Avoid extreme humidity conditions.</p> <p>- Pressure: Not relevant.</p> <p>- Shock: The product is not sensitive to shocks, but as a recommendation of a general nature should be avoided bumps and rough handling to avoid dents and breakage of packaging, especially when the product is handled in large quantities, and during loading and download operations.</p>
10.5	<p>INCOMPATIBLE MATERIALS: Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.</p>
10.6	<p>HAZARDOUS DECOMPOSITION PRODUCTS: # As consequence of thermal decomposition, hazardous products may be produced: formaldehyde.</p>

SECTION 11: TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2021/849 (CLP).

11.1 **INFORMATION ON HAZARD CLASSES AS DEFINED IN REGULATION (EC) NO 1272/2008 :****ACUTE TOXICITY:**

Dose and lethal concentrations for individual ingredients:	DL50 (OECD401) mg/kg bw Oral	DL50 (OECD402) mg/kg bw Cutaneous	CL50 (OECD403) mg/m ³ ·4h Inhalation
Hydrocarbons C9 aromatics	3592 Rat	3160 Rabbit	> 6193 Rat
Dimethoxymethane	6423 Rat	5708 Rabbit	> 20000 Rat
1,3-dioxolane	> 2000 Rat	68400 Rabbit	> 20650 Rat
Methanol	5626 Rat	15800 Rabbit	> 85300 Rat
Formic acid	730 Rat	> 2000 Rat	> 7850 Rat
Estimates of acute toxicity (ATE) for individual ingredients:	ATE mg/kg bw Oral	ATE mg/kg bw Cutaneous	ATE mg/m ³ ·4h Inhalation
Hydrocarbons C9 aromatics	-	-	-
Dimethoxymethane	-	-	-
1,3-dioxolane	-	-	20650 Vapours
Methanol	* > 100	* > 300	3000 Vapours
Formic acid	730	-	7850 Vapours

(*) - Point estimates of acute toxicity corresponding to the classification category (see GHS/CLP Table 3.1.2). These values are designed to be used in the calculation of the ATE for classification of a mixture based on its components and do not represent test results.

(-) - The components that are assumed to have no acute toxicity at the upper threshold of category 4 for the corresponding exposure route are ignored.

- No observed adverse effect level	NOAEL Oral mg/kg bw/d	NOAEL Cutaneous mg/kg bw/d	NOAEC Inhalation mg/m ³
1,3-dioxolane	75 Rat	-	903 Rat

- Lowest observed adverse effect level

Not available

INFORMATION ON LIKELY ROUTES OF EXPOSURE: ACUTE TOXICITY:

Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed	Criteria
Inhalation: Not classified	ATE > 20000 mg/m ³	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.



QUITAPINTURAS UNIVERSAL
Code : 12133



Version: 7

Revision: 28/02/2023

Previous revision: 16/12/2022

Date of printing: 28/02/2023

Skin: Not classified	ATE > 5000 mg/kg bw	-	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
Eyes: Not classified	Not available.	-	Not classified as a product with acute toxicity by eye contact (lack of data).	GHS/CLP 1.2.5.
Ingestion: Not classified	ATE > 5000 mg/kg bw	-	Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.

GHS/CLP 3.1.3.6: Classification of mixtures based on ingredients of the mixture (additivity formula).

CORROSION / IRRITATION / SENSITISATION :

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Respiratory corrosion/irritation: Not classified	-	-	Not classified as a product corrosive or irritant by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 1.2.6. 3.8.3.4.
- Skin corrosion/irritation: Not classified	-	-	Not classified as a product corrosive or irritant in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.2.3.3.
- Serious eye damage/irritation: Not classified	-	-	Not classified as a product corrosive or irritant in contact with eyes (based on available data, the classification criteria are not met).	GHS/CLP 3.3.3.3.
- Respiratory sensitisation: Not classified	-	-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.
- Skin sensitisation: Not classified	-	-	Not classified as a product sensitising by skin contact (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.

GHS/CLP 3.2.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.3.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.4.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

- ASPIRATION HAZARD:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Aspiration hazard: Not classified	-	-	Not classified as a product hazardous by aspiration (based on available data, the classification criteria are not met).	GHS/CLP 3.10.3.3.

GHS/CLP 3.10.3.3: Classification of the mixture when data are available for all components or only for some components.

SPECIFIC TARGET ORGANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Effects	SE/RE	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Neurological:	SE 	Optic nerve, CNS 	Cat.2	NEUROTOXIC: May cause optic nerve and central nervous system damage if ingested (loss of vision).	GHS/CLP 3.8.3.4

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

CMR EFFECTS:

- Carcinogenic effects:

It is not considered as a carcinogenic product.

- Genotoxicity:

It is not considered as a mutagenic product.

- Toxicity for reproduction:

Does not harm fertility. Does not harm the unborn child.

- Effects via lactation:

Not classified as a hazardous product for children breast-fed.

DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:

Routes of exposure

May be absorbed by inhalation of vapour, through the skin and by ingestion.

- Short-term exposure:



QUITAPINTURAS UNIVERSAL
Code : 12133



Version: 7

Revision: 28/02/2023

Previous revision: 16/12/2022

Date of printing: 28/02/2023

Exposure to solvent vapour concentrations in excess of the stated occupational exposure limit, may result in adverse health effects, such as mucous membrane and respiratory system irritation and adverse effects on kidneys, liver and central nervous system. Liquid splashes in the eyes may cause irritation and reversible damage. If swallowed, may cause irritation of the throat; other effects may be the same as described in the exposure to vapours. Causes burns to the skin or eyes by direct contact or to the digestive tract if swallowed. The mists of fine particles are skin and respiratory tract irritants. Causes serious eye damage. Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs if swallowed. May cause damage to optic nerve and central nervous system if swallowed.

- Long-term or repeated exposure:

Repeated or prolonged contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

INTERACTIVE EFFECTS:

Not available.

INFORMATION ABOUT TOXICOKINETICS, METABOLISM AND DISTRIBUTION:

- Dermal absorption:

This preparation contains the following substances for which dermal absorption can be very high: Methanol.

- Basic toxicokinetics:

Not available.

ADDITIONAL INFORMATION:

Not available.

11.2 INFORMATION ON OTHER HAZARDS:

Endocrine disrupting properties:

This product contains substances with endocrine disrupting properties under evaluation in a concentration equal to or greater than 0.1% by weight: Formic acid.

Other information:

No additional information available.

SECTION 12: ECOLOGICAL INFORMATION

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2021/849 (CLP).

12.1 TOXICITY:

- Acute toxicity in aquatic environment for individual ingredients	CL50 (OECD 203) mg/l · 96hours	CE50 (OECD 202) mg/l · 48hours	CE50 (OECD 201) mg/l · 72hours
Hydrocarbons C9 aromatics	9.2 - Fishes	3.2 - Daphniae	2.9 - Algae
Dimethoxymethane	1000 - Fishes	1200 - Daphniae	
1,3-dioxolane	95 - Fishes	772 - Daphniae	877 - Algae
Methanol	15400 - Fishes	24500 - Daphniae	8000 - Algae
Formic acid	130 - Fishes	540 - Daphniae	1240 - Algae

- No observed effect concentration	NOEC (OECD 210) mg/l · 28 days	NOEC (OECD 211) mg/l · 21 days	NOEC (OECD 201) mg/l · 72 hours
1,3-dioxolane	546 - Fishes	197 - Daphniae	877 - Algae
Formic acid		102 - Daphniae	

- Lowest observed effect concentration

Not available

ASSESSMENT OF AQUATIC TOXICITY:

Aquatic toxicity	Cat.	Main hazards to the aquatic environment	Criteria
- Acute aquatic toxicity: Not classified	-	Not classified as a hazardous product with acute toxicity to aquatic life (based on available data, the classification criteria are not met).	GHS/CLP 4.1.3.5.5.3.
- Chronic aquatic toxicity:	Cat.3	HARMFUL: Harmful to aquatic life with long lasting effects.	GHS/CLP 4.1.3.5.5.4.

CLP 4.1.3.5.5.3: Classification of a mixture for acute hazards, based on summation of classified components.

CLP 4.1.3.5.5.4: Classification of a mixture for chronic (long term) hazards, based on summation of classified components.

12.2 PERSISTENCE AND DEGRADABILITY:

- Biodegradability:

Not available.

Aerobic biodegradation for individual ingredients	COD mgO2/g	%DBO/DQO 5 days 14 days 28 days	Biodegradabilidad
Hydrocarbons C9 aromatics	3195	4,3 - -	Easy
Dimethoxymethane	1681	- - 1	Not easy



QUITAPINTURAS UNIVERSAL
Code : 12133



Version: 7

Revision: 28/02/2023

Previous revision: 16/12/2022

Date of printing: 28/02/2023

1,3-dioxolane		-	-	1,3	Not easy
Methanol	1420		69	85 99	Easy
Formic acid	695		15	90 92	Easy

Note: Biodegradability data correspond to an average of data from various bibliographic sources.

- [Hydrolysis:](#)

Not available.

- [Photodegradability:](#)

Not available.

12.3 [BIOACCUMULATIVE POTENTIAL:](#)

Not available.

Bioaccumulation for individual ingredients	logPow	BCF L/kg	Potential
Hydrocarbons C9 aromatics	3.3	69.9 (calculated)	Low
Dimethoxymethane	-0.19	3.2 (calculated)	No bioaccumulable
1,3-dioxolane	-0.37	3.2 (calculated)	No bioaccumulable
Methanol	-0.77	3.2 (calculated)	No bioaccumulable
Formic acid	-0.54	3.2 (calculated)	No bioaccumulable

12.4 [MOBILITY IN SOIL:](#)

Not available

Mobility for individual ingredients	log P _{oc}	Constant of Henry Pa·m ³ /mol 20°C	Potential
Hydrocarbons C9 aromatics	2,96	440 (calculated)	Low
Dimethoxymethane	0,74		No bioaccumulable
1,3-dioxolane	0,54	2,45 (calculated)	No bioaccumulable
Methanol	0,44		No bioaccumulable
Formic acid	-0,14		No bioaccumulable

12.5 [RESULTS OF PBT AND VPVB ASSESMENT:\(Annex XIII of Regulation \(EC\) no. 1907/2006:\)](#)

Does not contain substances that fulfil the PBT/vPvB criteria.

12.6 [ENDOCRINE DISRUPTING PROPERTIES:](#)

This product contains substances with endocrine disrupting properties under evaluation in a concentration equal to or greater than 0.1% by weight: Formic acid.

12.7 [OTHER ADVERSE EFFECTS:](#)

- [Ozone depletion potential:](#)

Not available.

- [Photochemical ozone creation potential:](#)

Not available.

- [Earth global warming potential:](#)

In case of fire or incineration liberates CO₂.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 [WASTE TREATMENT METHODS:Directive 2008/98/EC~Regulation \(EU\) no. 1357/2014:](#)

Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose at an authorised waste collection point. Waste should be handled and disposed in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.

[Disposal of empty containers:Directive 94/62/EC~2015/720/EU, Decision 2000/532/EC~2014/955/EU:](#)

Emptied containers and packaging should be disposed in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of emptying of the same, being the holder of the residue responsible for their classification, in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in itself.

[Procedures for neutralising or destroying the product:](#)

Controlled incineration in special facilities for chemical waste, in accordance with local regulations.



QUITAPINTURAS UNIVERSAL
Code : 12133



Version: 7

Revision: 28/02/2023

Previous revision: 16/12/2022

Date of printing: 28/02/2023

SECTION 14: TRANSPORT INFORMATION

14.1	<u>UN NUMBER OR ID NUMBER:</u> 1263
14.2	<u>UN PROPER SHIPPING NAME:</u> PAINT
14.3	<p><u>TRANSPORT HAZARD CLASS(ES):</u> <u>Transport by road (ADR 2021) and</u> <u>Transport by rail (RID 2021):</u></p> <p style="text-align: right;">FP<23°C, viscous according 2.2.3.1.4. <450 L (ADR) or 2.3.2.2. <30 L (IMDG) or 3.3.3.1.1. <30 L (IATA), VP<110 kPa50°C</p> <p>- Class: 3 - Packing group: III - Classification code: F1 - Tunnel restriction code: (D/E) - Transport category: 2, max. ADR 1.1.3.6. 333 L - Limited quantities: 5 L (see total exemptions ADR 3.4) - Transport document: Consignment paper. - Instructions in writing: ADR 5.4.3.4</p> <p><u>Transport by sea (IMDG 39-18):</u></p> <p>- Class: 3 - Packing group: III - Emergency Sheet (EmS): F-E,S_E - First Aid Guide (MFAG): 310,313 - Marine pollutant: No. - Transport document: Shipping Bill of lading.</p> <p><u>Transport by air (ICAO/IATA 2021):</u></p> <p>- Class: 3 - Packing group: III - Transport document: Air Bill of lading.</p> <p><u>Transport by inland waterways (ADN):</u> Not available</p>
14.4	<u>PACKING GROUP:</u> See section 14.3
14.5	<u>ENVIRONMENTAL HAZARDS:</u> # Not applicable.
14.6	<u>SPECIAL PRECAUTIONS FOR USER:</u> Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are upright and secure. Ensure adequate ventilation.
14.7	<u>MARITIME TRANSPORT IN BULK ACCORDING TO IMO INSTRUMENTS:</u> Not applicable.



SECTION 15: REGULATORY INFORMATION

15.1	<p><u>SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE:</u> The regulations applicable to this product generally are listed throughout this Safety Data Sheet. <u>Restrictions on manufacture, placing on market and use:</u> See section 1.2 <u>Tactile warning of danger:</u> If the product is intended for the public in general, a tactile danger sign is mandatory. The technical specifications for tactile warning devices shall conform with EN ISO standard 11683 relating to 'Packaging - Tactile warnings of danger - Requirements.' <u>Child safety protection:</u> Not applicable (the classification criteria are not met). <u>OTHER REGULATIONS:</u> <u>Control of the risks inherent in major accidents (Seveso III):</u> See section 7.2 <u>Other local legislations:</u> The receiver should verify the possible existence of local regulations applicable to the chemical.</p>
15.2	<u>CHEMICAL SAFETY ASSESSMENT:</u> A chemical safety assessment has not been carried out for this mixture.



QUITAPINTURAS UNIVERSAL
Code : 12133



Version: 7

Revision: 28/02/2023

Previous revision: 16/12/2022

Date of printing: 28/02/2023

SECTION 16 : OTHER INFORMATION

16.1 TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:Hazard statements according the Regulation (EU) No. 1272/2008~2021/849 (CLP), Annex III:

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H301 Toxic if swallowed. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H311 Toxic in contact with skin. H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage. H331 Toxic if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. EUH071 Corrosive to the respiratory tract. H370 Causes damage to optic nerve and central nervous system if swallowed. H371 May cause damage to optic nerve and central nervous system if swallowed.

Notes related to the identification, classification and labelling of the substances or mixtures:

Note B : Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

EVALUATION OF THE INFORMATION ON THE DANGER OF MIXTURES:

See sections 9.1, 11.1 and 12.1.

ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of Safety Data Sheets and labelling of products as well.

MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:

- European Chemicals Agency: ECHA, <http://echa.europa.eu/>
- Access to European Union Law, <http://eur-lex.europa.eu/>
- Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970).
- Threshold Limit Values, (AGCIH, 2021).
- European agreement on the international carriage of dangerous goods by road, (ADR 2021).
- International Maritime Dangerous Goods Code IMDG including Amendment 39-18 (IMO, 2018).

ABBREVIATIONS AND ACRONYMS:

List of abbreviations and acronyms that can be used (but not necessarily used) in this Safety Data Sheet:

- REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- CLP: European regulation on Classification, Labelling and Packaging of substances and chemical mixtures.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- ELINCS: European List of Notified Chemical Substances.
- CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials.
- SVHC: Substances of Very High Concern.
- PBT: Persistent, bioaccumulable and toxic substances.
- vPvB: Very persistent and very bioaccumulable substances.
- VOC: Volatile Organic Compounds.
- DNEL: Derived No-Effect Level (REACH).
- PNEC: Predicted No-Effect Concentration (REACH).
- LC50: Lethal concentration, 50 percent.
- LD50: Lethal dose, 50 percent.
- UN: United Nations Organisation.
- ADR: European agreement concerning the international carriage of dangerous goods by road.
- RID: Regulations concerning the international transport of dangerous goods by rail.
- IMDG: International Maritime code for Dangerous Goods.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.

SAFETY DATA SHEET REGULATIONS:

Safety Data Sheet in accordance with Article 31 of Regulation (EC) No. 1907/2006 (REACH) and Annex of Regulation (EU) No. 2020/878.

HISTORIC: REVISION:

Version: 5	21/02/2022
Version: 6	16/12/2022
Version: 7	28/02/2023

Changes since previous Safety Data Sheet:

Legislative, contextual, numerical, methodological and normative changes since the previous version of the present Safety Data Sheet are identified by #.

The information of this Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.